

DEX-O-TEX

System Description Sheet

ELASTATEX 500 URETHANE DECKING

Promenade and Roof Deck Waterproofing and Surfacing System



1. PRODUCT DESCRIPTION

A. COMPOSITION

Elastatex 500 Urethane Decking is a solvent-free, fluid-applied, elastomeric waterproofing and surfacing system that is ideal for waterproofing balconies, walking decks and semi-level roof decks aboard ships.

Elastatex 500 system consists of a specially formulated moisture-cure aromatic urethane, broadcast rubber granules and a durable aliphatic urethane polyurea blended elastomeric topcoat.

The topcoat is a tough, ultraviolet light resistant aliphatic urethane polyurea blend and it is available in standard colors.

It is turned up against building, walls, parapets, etc. to form an integral waterproof membrane.

Designed primarily as a waterproof system for surfaces, such as promenade decks, balconies, sun decks and play roofs, etc. Elastatex 500 is also used as a protective covering for renovating elevated concrete, including: cracked concrete, promenade decks, pool decks, etc. Surfaces over which Elastatex 500 may be installed include: new and existing concrete, metal and plywood. Consult Crossfield regarding other surfaces.

B. TYPICAL USES

It has excellent crack-bridging and low temperature flexibility characteristics. It is designed to protect concrete surfaces from spalling and scaling associated with freeze/thaw induced damage, including waterproofing promenade decks, sun decks, patios, roofs, rooftop tennis courts, balconies, and pedestrian traffic surfacing.

C. ADVANTAGES AND LIMITATIONS

ADVANTAGES:

1. Monolithic, including integral flashing.
2. Resilient and comfortable underfoot.
3. Reduces sound transmission to adjacent areas.
4. Non-flammable during installation.
5. Environmentally safe.
6. Zero VOC, exceeds all federal, state and agency VOC (volatile organic compound) requirements.
7. Installed only by Professional Factory Trained Dex-O-Tex Contractors.

LIMITATIONS:

1. Substrates must be dry when material is applied.
2. Not designed for interior use.
3. Moisture vapor transmission (MVT) in excess of 3.0 lbs/1000 sq/ft/per 24 hr period per ASTM F1869, may result in delamination, discoloration or improper curing. Use Dex-O-Tex VaporControl™ Primer 100 over substrates, which have MVT emissions that exceed these limits. Consult with Crossfield prior to using VaporControl Primer 100 if moisture vapor transmission exceeds 15 lbs/1000 sq/ft/per 24 hr period per ASTM F1869.

2. TYPICAL PHYSICAL PROPERTIES at 75°F (24°C)

A. Weight	0.46 lbs. per sq. ft.
B. Thickness (typical)	1/16" (1,58 mm)
C. Tensile Elongation ASTM D412	500%
D. Tensile Strength ASTM D412	1,050 psi
E. Waterproofness (sample exposed to 50 psi water pressure for one hour)	No Water Transmission
F. Adhesion ASTM 2240, Shore A	60-70
G. Crack Bridging and Low Temperature Flexibility ASTM C836	Complies
H. Microbial Resistance ASTM G21	Passes

3. OVERVIEW OF INSTALLATION STEPS

- A. Prepare surface by careful and thorough removal of laitance, grease, concrete curing agents and foreign matter. Consult Crossfield for instructions on acid etching or shot blasting requirements.
- B. Apply epoxy primer by roller.
- C. Apply Elastatex basecoat by trowel and broadcast rubber granules into cured basecoat.
- D. Apply pigmented topcoat by roller or airless spray.

4. PRODUCT AVAILABILITY

Crossfield Products Corp. maintains offices and/or factories at all addresses listed below. Factory Trained Contractors are established in all major trading areas in the United States, Canada and various European, Latin American and Far East nations.

5. SKID RESISTANCE and CLEANABILITY

In general the more aggressive the finished surface the greater the coefficient of friction and corresponding skid resistance, the more difficult to clean. The smoother the finished texture the easier the surface is to clean, but there is a loss of skid resistant properties.

6. CLEANING

Cleaning and disinfecting compounds and cleaning techniques can affect the color, gloss, texture and performance of the system. As a precautionary step, Crossfield recommends that the end-user test their cleaning and disinfecting compounds on a sample or on a small, out of the way finished area, utilizing the intended cleaning technique prior to cleaning the entire surface area. If no deleterious effects are observed, the procedure can be continued. If the cleaning and disinfecting compounds or cleaning techniques damage the system, modification of the cleaning material or techniques will be required. Contact your Representative for additional information.

7. SPECIFICATION ASSISTANCE

Consult Crossfield Products Corp. for specification assistance, detailing, etc. This consultation is highly recommended prior to specification.

8. CHEMICAL RESISTANCE

See Crossfield Products Corp's., Chemical Resistance Guidelines for chemical resistance of a product or system, as well as the types of test performed:

- ASTM C868 Standard Test Method for Chemical Resistance of Protective Lining.
- ASTM C267 Standard Test Method for Chemical Resistance of Mortars, Grouts, and Monolithic Surfacing and Polymer Concretes.
- ASTM D1308 Standard Test Method for Effect of Household Chemicals on Clear and Pigmented Organic Finishes
- Crossfield Products Corp. Proprietary Testing

Note: Chemical resistance is a functional test, usually limited to changes in weight or thickness measured in loss or gain and does not evaluate subject aesthetic issues. To determine aesthetic issues, Crossfield recommends testing the products or system in accordance with intended end use.

9. TESTING

The technical data contained herein is the result of tests made in Crossfield's laboratories or in independent laboratories using small scale equipment, following generally accepted trade practices. Although this information is believed to be true and accurate, the use of different equipment for testing under dissimilar conditions or the testing of samples produced under dissimilar conditions may develop substantially different results.

LIMITED WARRANTY

NO WARRANTY SHALL BE EFFECTIVE UNTIL THE TERMS AND CONDITIONS OF SALE SET FORTH IN CROSSFIELD PRODUCTS CORP. INVOICES ARE MET.

Crossfield Products Corp. warrants to the purchaser of its products that such products are free from manufacturing defect. Crossfield does not warrant or guarantee the workmanship performed by any person or firm installing its products. Crossfield's obligation under this warranty is limited solely to the original purchaser and solely to the remedy of replacement in kind of any product which Crossfield sold which may prove defective in manufacture within one year from date of installation, provided said product was stored correctly and installed within the product's shelf life, by the original purchaser and which Crossfield's examination shall disclose to Crossfield's satisfaction to be thus defective.

IN NO EVENT SHALL CROSSFIELD PRODUCTS CORP. BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. THIS WARRANTY IS EXPRESSLY GIVEN IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR USE AND ALL OTHER OBLIGATIONS OR LIABILITIES ON CROSSFIELD'S PART, AND WE NEITHER ASSUME NOR AUTHORIZE ANY PERSON OR PERSONS TO ASSUME FOR US ANY OTHER LIABILITY IN CONNECTION WITH SALE OF A CROSSFIELD PRODUCT. THIS WARRANTY SHALL NOT APPLY TO ANY OF CROSSFIELD'S PRODUCTS, WHICH HAVE BEEN SUBJECT TO ADULTERATION, ALTERATION ABUSE OR MISUSE. CROSSFIELD PRODUCTS CORP. MAKES NO WARRANTY WHATSOEVER IN RESPECT TO ACCESSORIES, PARTS OR MATERIAL NOT SUPPLIED BY CROSSFIELD PRODUCTS CORP., WHICH ARE USED IN CONNECTION WITH ITS PRODUCTS. THE TERM "ORIGINAL PURCHASER" IN THIS WARRANTY MEANS THAT PERSON, CORPORATION OR ENTITY TO WHOM CROSSFIELD PRODUCTS CORP. SOLD ITS PRODUCTS. ANY ACTION TO ENFORCE ANY WARRANTY OR FOR BREACH OF CONTRACT OR ARISING OUT OF ANY CLAIM AGAINST CROSSFIELD PRODUCTS CORP. SHALL BE COMMENCED AND MAINTAINED ONLY IN A COURT OF COMPETENT JURISDICTION IN THE CONTINENTAL UNITED STATES OF AMERICA. THE PURCHASER ACCEPTS THESE TERMS AND CONDITIONS, AND HEREBY EXPRESSLY WAIVES ANY CLAIM TO ADDITIONAL DAMAGES.

CAUTION: ALWAYS KEEP OUT OF THE REACH OF CHILDREN.



DEX-O-TEX Product Line Crossfield Products Corp.

**Western Division
3000 E. Harcourt Street
Rancho Dominguez, CA 90221
310-886-9100
310-886-9119 fax**

**Eastern Division
140 Valley Road
Roselle Park, NJ 07204
908-245-2800
908-245-0659 fax**

www.dexotex.com